

10-27-00

A



ATTORNEY'S DOCKET NO.
062891.0482

PATENT APPLICATION

1



APPLICATION FOR U.S. PATENT UNDER 37 C.F.R. § 1.53(b)
TRANSMITTAL FORM

Box Patent Application
ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

Inventor or Application Identifier:
Dantu, et al.

Entitled: METHOD AND SYSTEM FOR PROVIDING SERVICES FOR
WIRELESS DATA CALLS

Enclosed are:

- ☒ Specification (47 Total Pages)
☒ Drawing(s) (25 Total Sheet(s) of ☒ Formal ☐ Informal)
☒ Combined Declaration and Power of Attorney
☒ Newly executed (original or copy)
☐ Copy from a prior application
(for continuation/divisional only)

- ☒ An Assignment of the invention to Cisco Technology, Inc. is attached.
A separate cover sheet in compliance with 37 C.F.R. § 3.28 and § 3.31 is included
with an Assignment recordal fee of \$40.00 pursuant to 37 C.F.R. § 1.21(h).

☒ Certificate of Mailing

☒ Return Receipt Postcard

Applicant is:

- ☒ Large Entity
☐ Small Entity
☐ Small Entity Statement enclosed
☐ Small Entity Statement filed in prior application.
Status still proper and desired.

ATTORNEY'S DOCKET NO.
062891.0482

PATENT APPLICATION

2

The accompanying application is:

☒ Original.


☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP)

of prior application No. _____ which is hereby incorporated by reference therein.

FEE CALCULATION					FEE
	Number		Number Extra	Rate	Basic Fee
					\$ 710.00
Total Claims:	102	-20 =	82	X \$18 =	\$ 1,476.00
Independent Claims	5	- 3 =	2	X \$80 =	\$ 160.00
TOTAL FILING FEE =					\$ 2,346.00

☒ Enclosed is a check in the amount of \$2,346.00 to satisfy filing fee requirements under 37 C.F.R. § 1.16. Please charge any additional fees or credit any overpayment to Deposit Account No. 02-0384 of BAKER BOTTS L.L.P. A duplicate copy of this sheet is enclosed.

Respectfully submitted,
BAKER BOTTS L.L.P.
Attorneys for Applicant



Terry J. Stalford
Reg. No. 39,522
October 25, 2000

Correspondence Address:
Terry J. Stalford, Esq.
Baker Botts L.L.P.
2001 Ross Avenue
Dallas, Texas 75201-2980

Tel. 214.953.6477
Fax. 214.661.4477

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



In re Application of: Dantu, et al.

Date Filed: October 25, 2000

Title: METHOD AND SYSTEM FOR PROVIDING
SERVICES FOR WIRELESS DATA CALLS

BOX PATENT APPLICATION

Honorable Assistant Commissioner

For Patents

Washington, D.C. 20231

Dear Sir:

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that the attached Application Transmittal Form, Patent Application, executed Declaration and Power of Attorney, twenty-five (25) sheets of Formal Drawings, Assignment, Assignment Cover Sheet, firm checks in the amount of \$2,346.00 to cover the application filing fee, and \$40.00 assignment recordation fee, and this Certificate of Mailing are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on this 25th day of October, 2000 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Willie Jiles

Willie Jiles

Express Mail Receipt
No. EL501048564US
Attorney's Docket:
062891.0482

METHOD AND SYSTEM FOR PROVIDING
SERVICES FOR WIRELESS DATA CALLS

TECHNICAL FIELD OF THE INVENTION

This invention relates generally to the field of
wireless communications, and more particularly to a
5 method and system for providing services for wireless
data calls.

BACKGROUND OF THE INVENTION

Traditional wireless networks include a number of base stations (BST) and one or more mobile switching centers (MSC). The BSTs each cover a geographic region, or cell of the wireless network and communicate with mobile telephones in the cell. The MSCs provide switch and soft handoff functionality for the wireless network. To support data calls, the wireless network includes a data interworking function (IWF). The IWF connects the wireless network to the Internet or other network.

Current wireless networks are optimized for real-time voice traffic, despite the growing demand for data traffic. For voice traffic, wireless networks typically provide call forwarding, call blocking, call waiting, star dialing and other services. These services enhance the utilization of mobile telephones and allow network operators to differentiate their services.

Due to the differences between voice and data traffic, many wireless voice services are not applicable to data traffic. In addition, service provision nodes for wireless voice and other telephony traffic on the Public Switched Telephone Network (PSTN) are not generally accessible to data calls. Accordingly, wireless network have no provisionable services for data calls, which are differentiated based on quality of service (QoS) parameters.

SUMMARY OF THE INVENTION

The present invention supplies a method and system for providing services for wireless data calls that substantially reduce or eliminate problems and disadvantages associated with previous systems and methods. In particular, call-based and network-based triggers are provided for data calls to support location, filtering and billing based services for data calls.

In accordance with one embodiment of the present invention, a method and system for providing services for wireless data calls includes monitoring a wireless data call for a predefined event associated with a service for the wireless data call. The service is initiated for the wireless data call in response to detecting the predefined event for the data call.

More specifically, in accordance with a particular embodiment of the present invention, the predefined event may be a uniform resource locator (URL) match or change, an excessive use of transmission or time resources of the wireless network or may be based on a location of a mobile device for the wireless data call. In this and other embodiments, the wireless network may be monitored for network-based events associated with network directed services for the wireless data call. The network directed services are initiated for the wireless data call in response to detecting the network-based event for the wireless data call. The network-based event may be a data alert or change in a status of network facilities.

Technical advantages of the present invention include supplying a method and system for providing services for data calls. In particular, call-based and network-based services are provisioned for a data call at

call setup. Location, filtering and billing services are provided for the data call based on dynamic, real-time content of the data call and/or network activity.

Another technical advantage of the present invention includes providing an improved wireless network. In particular, services are provided for voice and data calls to allow a network operator to differentiate both voice and data services for mobile subscribers as well as services provided by portals. In addition, the services support shopping and trading to facilitate e-commerce marketing plans and allow network operators to engage in fee sharing for revenue generation and deployment of wireless Internet services.

Still another technical advantage of the present invention includes providing improved services for a wireless call. The services include content monitoring, controlling web sessions and blending existing voice services on top of these data services. In addition, mobility and location based services are provided as well as interactive gaming services.

Other technical advantages of the present invention will be readily apparent to one skilled in the art from the following figures, description, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and its advantages, reference is now made to the following description, taken in conjunction with the company drawings, in which:

FIGURE 1 is a block diagram illustrating layers of an all Internet protocol (IP) wireless communications network in accordance with one embodiment of the present invention;

FIGURE 2 is a block diagram illustrating details of the wireless network of FIGURE 1 in accordance with one embodiment of the present invention;

FIGURES 3A-B are flow diagrams illustrating methods for providing services for data calls in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 4A-C are a call flow diagram illustrating a methodology for mobile initiated call setup and clear for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 5A-B are tables illustrating messages for provisioning data services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 6A-B are tables illustrating messages for initiating data transfer for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 7A-B are tables illustrating messages for terminating data transfer for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 8A-B are tables illustrating messages for data clear services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

5 FIGURES 9A-B are tables illustrating messages for forward direction transmission excess services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

10 FIGURES 10A-B are tables illustrating messages for reverse direction transmission excess services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

15 FIGURES 11A-B are tables illustrating messages for time excess services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

20 FIGURES 12A-B are tables illustrating messages for uniform resource locator (URL) matching services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

25 FIGURES 13A-B are tables illustrating messages for location change services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

30 FIGURES 14A-B are tables illustrating messages for multiple match services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

 FIGURES 15A-B are tables illustrating messages for URL change services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

FIGURES 16A-B are tables illustrating messages for data alert services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention;

5 FIGURES 17A-B are tables illustrating messages for facility status services for a data call in the wireless network of FIGURE 2 in accordance with one embodiment of the present invention; and

10 FIGURES 18A-U are tables illustrating parameters for the service messages of FIGURES 5-17 in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 illustrates a wireless communications network 10 in accordance with one embodiment of the present invention. In this embodiment, the wireless network 10 is a multiple layer cellular network in which terrestrial wireless transmission originates in geographically delimited cells. It will be understood that the present invention may be used in connection with other suitable wireless networks.

Referring to FIGURE 1, the wireless network 10 includes a service layer 12, a control layer 13, a wireline router layer 14, a wireless router layer 16, and a physical layer 18. The service layer 12 provides network services for voice and data calls. Administrative services for establishing and maintaining calls include call server, bandwidth broker, policy server, service level agreement (SLA) manager, billing server, home location register (HLR), home subscriber server (HSS), domain name server (DNS), dynamic host configuration protocol (DHCP), media gateway (MGW), signaling gateway (SGW), legacy servers such as mobile switching center (MSC), base station controller (BSC), serving GPRS serving node (SGSN), voicemail server (VMS), fax/modem server, short message center (SMSC), conferencing facilities and transcoders. As described in more detail below, network services for data calls include location, filtering and billing based services. As also described in more detail below, the control layer 13 provides a quality of service (QoS) manager, mobility manager, location manager, call agent, media gateway controller (MGC), power manager, authentication,

authorization, and accounting (AAA), and other suitable agents and managers.

The wireline router layer 14 may be a wireline specific Internet protocol (IP) layer. The wireline router layer 14 includes a wireline router network having a plurality of wireline routers 20 interconnected by physical wireline links 22. The wireline routers 20 receive and transmit traffic on the wireline links 22. The wireline router network forms the core IP network and may be the Internet, intranet, extranet, or other suitable local, wide area network, or combination of networks.

The wireless router layer 16 may be a wireless-specific IP layer. The wireless router layer 16 includes a wireless router network having a plurality of wireless routers 30 interconnected by wireless router links 32. The wireless router links 32 may be microwave or other wireless links or virtual or other suitable flows configured in the wireline links 22 of the wireline IP layer 14. Each wireless router 30 may be implemented as a discrete node independent of a wireline router 20 or may be implemented as a logical layer in a wireline router 20. As used herein, each means every one of at least a subset of the identified items.

The wireless routers 30 intercommunicate traffic and control information over the wireless router links to perform call set up, resource reservation, mobility management, soft handoff, air bandwidth allocation and routing. As described in more detail below, the wireless router links 32 may comprise multi-protocol label switch (MPLS) or other suitable virtual tunnels formed in the wireline links 22. The wireless routers 30 may be self-

configuring as described in co-owned U.S. Patent Application Serial Number 09/513,090, entitled "Method and System for Configuring Wireless Router and Network," which is hereby incorporated by reference.

5 The wireless routers 30 are connected to the wireline routers 20 by wireline links. In this way, the wireless routers 30 provide connectivity from the wireless portion of the network 10 to the wireline portion of the network 10 via circuit switched and packet
10 switched data protocols. Thus, the wireless routers 30 receive and route traffic over both wireline and wireless links 22 and 32.

 The physical layer 18 includes a series of overlapping cells 40. Each cell 40 is supported by a
15 corresponding wireless router 30 and may be subdivided into a plurality of geo-location areas 42. The geo-location areas 42 are each a defined area in which bandwidth may be allocated to mobile devices 44. Further information regarding the geo-location areas and
20 allocation of bandwidth within geo-location areas is described in co-owned U.S. Patent Application Serial Number 09/466,308, entitled "Method and System for Allocating Bandwidth in a Wireless Communications Network," filed December 17, 1999, which is hereby
25 incorporated by reference.

 In the wireless network 10, each wireless router 30 provides a radio frequency (RF) link for mobile devices 44 within a corresponding cell 40. The wireless RF link to the mobile devices 44 in the cell 40 may be based on
30 established technologies, or standards such as IS-54 (TDMA), IS-95 (CDMA), GSM and AMPS, 802.11 based WLAN, or new upcoming technologies such as CDMA 2000 and W-CDMA or

proprietary radio interfaces. The mobile devices 44 may be cell phones, data phones, data devices, portable computers, handheld devices, network appliances or any other suitable device capable of communicating information over a wireless link.

In operation, the wireless routers 30 each have a defined bandwidth with which to communicate with the mobile devices 44 in the cells 40. The bandwidth is used by the wireless router 30 and the mobile devices 44 to communicate voice and data information. The supported bandwidth is a function of various factors such as frequency reuse, carrier to interface ratio, bit-energy to noise ratio, effective bit-rate per connection and the like. The bandwidth available to allocate to certain flows is geo-location dependent, and time dependent based on current usage of other flows in the geo-neighborhood.

The wireless routers 30 each allocate bandwidth within a corresponding cell 40, route traffic to and from the cell 40, and track the location of the mobile devices 44 within the cell 40. The position of a mobile device 44 may be determined using network-assist, global position systems (GPS) and radio frequency fingerprinting. Preferably, the positioning technique provides fast and accurate information with respect to the location of the mobile device 44 to minimize acquisition time for position information.

As mobile users move from cell 40 to cell 40, the wireless routers 30 perform soft handoff operations to provide continuous connectivity within the network. The wireless routers 30 provide additional call control and switching functionality to provide an all-IP wireless access network with seamless interworking with core IP

network elements in a distributed control architecture. Further information regarding operation of the wireless routers is described in co-owned U.S. Patent Application Serial No. 09/513,914, entitled "Wireless Router and Method for Processing Traffic in a Wireless Communications Network," filed February 25, 2000, which is hereby incorporated by reference.

FIGURE 2 illustrates details of the wireless network in accordance with one embodiment of the present invention. In this embodiment, the radio frequency (RF), agent, broker and gateway functionality is implemented in an integrated wireless router 30. The wireless router 30 comprises logic stored in a computer processable medium for implementing functionality of the router 30. The logic may comprise software stored in a computer readable medium and/or instructions stored or encoded in hardware. It will be understood that the RF, agent, broker and gateway functionality may be distributed within the wireless network.

Referring to FIGURE 2, a wireless office, or wireless access system 50 spans a session/control layer 52, a network/transport layer 54 and an access layer 56. The wireless access system 50 may be an enterprise or public carrier network device and includes a RF management system 60, an gateway 62, and a wireless signaling management system 64. The RF management system 60 is in the access layer 56 while the gateway 62 is in the network/transport layer 54. The wireless signaling management system 64 is in the session/control layer 52.

The RF management system 60 includes a base station (BST) and a base station controller (BSC) and/or other suitable equipment communicating wireless traffic with

the mobile devices 44 in a corresponding cell 40 and/or neighboring cells. The RF management system, or RF station 60 may communicate with the mobile devices 44 using TDMA, CDMA, GSM, W-CDMA, CDMA 2000 and other suitable standards. In operation, the RF station 60 communicates traffic with the gateway 62 over real-time transport protocol (RTP) and other suitable protocol voice and data channels 65.

The gateway 62 is an air gateway for wireless traffic and processes and forwards traffic from the RF station 60 to an appropriate voice or data network and from a voice or data network to the RF station 60. In one embodiment, the air gateway 62 processes and forwards data traffic to the Internet or other Internet protocol (IP)/multiple protocol label switch (MPLS) network 70 or a wireless access protocol (WAP) gateway 72 for a home agent corporate virtual private network (VPN). The IP/MPLS network 70 may include one or more wireless portals 74. The air gateway 62 processes and forwards voice traffic to a voice gateway 76, and from the voice gateway 76 to a macro mobile switch controller (MSC) 78 of a legacy system or a Class 5 switch of a Public Switch Telephone Network (PSTN) 80. The data and voice networks are in the network/transport and access layers 54 and 56 of the wireless network.

The wireless signaling management system 64 comprises one or more discrete components and includes an air broker 66 and an air agent 68 that provide resource and mobility management for calls in the wireless network. In one embodiment, the wireless signaling management system 64 communicates with the RF station 60 using media gateway control protocol (MGCP) 2.1, or A+

protocols. In this embodiment, the wireless signaling management system 64 communicates with the air gateway 62 using the MGCP and Common Open Policy Services (COPS) or radius protocols.

5 To provide and support services for voice and data calls, the wireless signaling management system 64 communicates with a call agent 82 in the session/control layer 52 and with service agents 84 in a legacy system service layer 86. The call agent 82 further communicates
10 with the voice gateway 76 and with an SS7 telephony node 88, which communicates with the PSTN 80. In a particular embodiment, the wireless signaling management system 64 communicates with the call agent 82 using an extended session initiation protocol (ESIP). In this embodiment,
15 the call agent 82 communicates with the voice gateway 76 using the MGCP protocol while the voice gateway 76 communicates with the PSTN network 88 using the Integrated Services Digital Network (ISDN) User Part (ISUP) protocol.

20 The service agents 84 include a macro home location register (HLR) agent 90, a mobile switching gateway (MSG) (HLR) agent 92, an intelligent service platform (ISCP) agent 94 and an AAA/radius agent 96. As described in more detail below, the ISCP agent 94 provides
25 programmable and intelligent services for data calls. The AAA/radius agent 96 provides administrative services for the wireless access device 50. In a particular embodiment, the macro HLR agent 90 communicates with the MSG agent 92 using an IS41D protocol. In this
30 embodiment, the MSG agent 92 communicates with the wireless signaling management system 64 using the IS41D protocol, the ISCP agent 94 communicates with the

wireless signaling management system 64 using the extended mark-up language (XML) protocol and the AAA/radius agent 96 communicates with the wireless signaling management system using the Lightweight Directory Access Protocol (LDAP) protocol. It will be understood that components in each of the layers 52, 54, 56 and 86 may communicate with other components using other suitable protocols without departing from the scope of the present invention.

As described in more detail below, the air gateway 62 and the wireless signaling management system 64 establish and maintain, or carry, voice and data calls in the wireless network. At the time a data call is established, service triggers are retrieved from the service agents 84 for the data call and stored in the air gateway 62 and/or air agent 68. The air gateway 62 and air agent 68 monitor content of the data call to provide filtering, prioritization, customization, and localization services. When conditions of a service trigger are met, the triggers are fired to service logic which may send alerts to the mobile user, control access to network resources and/or alter billing for the data call. The service logic may be downloaded with the triggers or stored in the service agents 84 or other suitable element. If the Service Logic is downloaded with the triggers, the ISCP agent 84 need not be notified of trigger events.

FIGURE 3A is a flow diagram illustrating a method for providing services for data calls in a wireless network. Referring to 3A, the method begins at step 130 in which a wireless data call is established. The wireless data call 130 may be established through a

number of discrete steps performed at the same time or at different times in the wireless network.

Proceeding to step 132, services events for the data call are loaded into a call monitoring system for the data call. The monitoring system is operable to identify the service events based on network activity and/or content of the data call. At step 134, the monitoring system monitors the data call in the network for service events.

At step 136, services are performed in response to the occurrence of associated events in the network and/or the content of the data call. One or more services may be performed during the duration of each data call. At step 138, the data call is terminated by the mobile device 44 and/or the network. Step 138 leads to the end of the process by which services are provided for wireless data calls.

FIGURE 3B is a flow diagram illustrating a method for providing services for data calls in a wireless network in accordance with a particular embodiment of the present invention. In this embodiment, the services comprise prepaid calling card services, location-based services, web filtering services, quality of service (QoS) based billing services, URL-based billing services, address-based services, and announcement services. The prepaid calling card services may comprise volume limited Internet or other network access services and time limited Internet or other network access services. The web filtering services may comprise access or denial to a list of websites and/or automatic website redirection. It will be understood that other suitable services may be provided for data calls through the air gateway 62 and/or

air agent 64 without departing from the scope of the present invention.

Referring to FIGURE 3B, the method begins at step 150 upon an origination message for a data call from a mobile device 44. A wireless data call is a communication session including a mobile device 44 in which non-voice and/or non-real-time information is exchanged between the mobile device 44 and a distinct device. The wireless data call may be conducted with a computing device over the Internet and include part or all non-real time data. At step 152, the data call requested by the mobile device 44 is set up. As previously described, the call is set up by the air gateway 62 in connection with the wireless signaling management system 64.

Next, at step 154, service triggers for the data call are established. The service triggers may be established by the air agent 68 accessing the ISCP agent 94 and/or other service agents 84 to identify and download service triggers for that data call. The service triggers for a data call may be identified by the phone number of the mobile device for the data call or based on a profile of the mobile device 44, access technology, user or other characteristic associated with the data call. The service triggers are stored in the air gateway 62 and/or the air agent 68.

Proceeding to step 156, data transfer is started for the data call. During the data call at state 160, the air gateway 62 and/or air agent 68 monitors content of the data call and/or the wireless network for service triggers. In response to detection of a service trigger, the air gateway 62 and/or air agent 68 initiate an

associated service by launching or signaling to launch the associated service logic. As used herein, in response to means performing a specified action upon at least the occurrence of the identified event. The action
5 may directly follow the event or follow an intervening action.

In response to a match trigger 162 during the data call, state 160 transitions to step 164. At step 164, service logic associated with the match trigger is
10 performed. The match may be a URL match, a source and/or destination IP or other suitable address match, part number match or based on other suitable criteria. The services may comprise web filtering, including access or denial to a list of websites or automatic website
15 redirection and/or URL-based billing. Upon completion of the service, step 164 transitions back to state 160 in which the data call is monitored for further service triggers.

In response to a new address trigger 172 during the data call, state 160 transitions to step 174. At step
20 174, service logic for the new address trigger is performed. The new address may be a new URL address, source and/or destination IP or other suitable address, part number or other suitable address criteria. The
25 service logic may comprise web filtering and URL-based billing services. Upon completion of the service logic, step 174 returns to state 160 in which the data call is monitored for additional service triggers.

In response to a new location trigger 182 during the data call, state 160 transitions to step 184 in which
30 service logic associated with the trigger is performed. The service logic may comprise location-based services.

Upon completion of the service logic, step 184 returns to state 160 in which the data call is monitored for additional service triggers.

5 In response to a facility change trigger 192 during the data call, state 160 transitions to step 194. At step 194, service logic associated with the trigger is performed. The service logic may comprise announcement and other suitable services. Upon completion of the service logic, step 194 returns to state 160 in which the data call is monitored for additional service triggers.

10 In response to a transmission excess trigger 202 during the data call, state 160 transitions to step 204. At step 204, service logic associated with the trigger is performed. The service logic may comprise prepaid calling card services for volume limited Internet access in the forward and/or reverse directions. Upon completion of the service logic, step 204 returns to state 160 in which the data call is monitored for additional service triggers.

20 In response to a time excess trigger 212 during the data call, state 160 transitions to step 214. At step 214, service logic associated with the trigger is performed. The service logic may comprise prepaid calling card services for time limited Internet access and other suitable services. Upon the completion of the service logic, step 214 returns to state 160 in which the data call is monitored for additional service triggers.

25 In response to a multimatch trigger 222 during the data call, state 160 transitions to step 224. The multimatch may be the occurrence, together or separately, of any combination of specified triggers or the occurrence of one or more of a set of triggers. At step

224, service logic associated with the trigger is performed. The service logic may comprise prepaid calling card, location-based, web filtering, billing and other suitable services. Upon completion of the service logic, step 224 returns to state 160 in which the data call is monitored for additional service triggers.

In response to a network-based trigger 232 during the data call, state 160 transitions to step 234. The network-based trigger may be the status of the system or a component in the system. At step 234, the service logic is performed for the trigger. Service logic may comprise announcements, including advertisements and news delivery, data cleans or other suitable services. Upon completion of the service logic, step 234 returns to state 160 in which the data call is monitored for further service triggers.

In response to a data end trigger 240, state 160 transitions to step 242. At step 242, the data session for the call is terminated. Step 242 leads to the end of the process by which filtering, prioritization, customization and location services are provided for a data call based on the content of the data call and/or network-based events.

FIGURES 4A-C are call flow diagrams illustrating methodology for mobile initiated call set up and clear for a data call in a wireless network in accordance with one embodiment of the present invention. In this embodiment, content, signaling, messages, and/or triggers are sent and received between the mobile device 44, the RF station 60, air agent 68, air gateway 62, call agent 82, and MSG/ISCP service agents 84. It will be understood that data calls may be otherwise set up,

provisioned with services, conducted and cleared without departing from the scope of the present invention.

Referring to FIGURES 4A-C, during call set up, a data origination (DATAORG) request is generated by the air agent 64 and transmitted to the MSG/ISCP service agents 84 for service triggers. The MSG/ISCP service agents 84 return the service triggers (dataorg) for the data call to the air agent 64. After channel assignment is complete, the traffic channel is set up. After traffic channel set up, the RTPs or other suitable protocol paths are set up between the base station 60 and the air gateway 62. Triggers are provided from the air agent 64 to the air gateway 62 using the COPS policy update. The data call may be released by the mobile device 44 with a release order signal to the RF station 60 and/or by the network with a data end signal to the air agent 68.

During a data session, data origination (dataorg), data begin (databegin), data end (dataend), URL match (URLmatch), location change (locchng), data clear (dataclear), forward transmission excess (fwdbytext), reverse transmission excess (revbytextd), time excess (timeexd), URL change (URLchng), multiple conditions matched (multimatch), data alert (dataalert), and facility change (facchng) triggers may be provided for the data call. The dataorg comprises an origination request for a data session and a reply of a list of triggers from service logic. The databegin trigger monitors a data call for start of a data session and triggers service logic. The dataend trigger monitors the data call for an end of a data session and triggers service logic.

The URLmatch trigger monitors the mobile user accessing a particular URL and triggers service logic. The locchng trigger monitors the mobile user moving to a new location such as another cell and triggers service logic. The dataclear trigger is from the ISCP agent 94 to the air agent 68 and is used to clear a data session. The fwdbytext trigger monitors transmissions exceeding a defined number of bytes in a forward direction, or path, and is sent from the air agent 68 to the ISCP agent 94. The revbytext trigger monitors transmissions exceeding a defined number of bytes in the reverse direction and is sent from the air agent 68 to the ISCP agent 94. The timeexd trigger monitors sessions time excesses and is sent from the air agent 68 to the ISCP agent 94.

The URLchng trigger monitors mobile users accessing a new URL and triggers service logic. The multimatch trigger monitors multiple conditions and is sent from the air agent 68 to the ISCP agent 94 when one or more and/or all of the conditions are matched. The dataalert trigger alerts the mobile user with a specific content such as a stock quote, advertisement or news and is sent from the service logic to the mobile user. The faclchng trigger monitors changes in the status of facilities such as handoffs to other air gateways 62, failure of links, routes, QoS and depletion of any resources.

FIGURES 5-17 illustrate exemplary messages for providing services for data calls in accordance with a particular embodiment of the present invention. The fields, field type, and field comments are provided for each message. Messages are sent from the air agent 68 to the ISCP and/or other service agent 84 and in the opposite direction. These messages are sent due to

triggers that are set either in the profile of the mobile device 44 or downloaded during the session establishment phase. These triggers are activated during the beginning of the session, middle of the session or termination of the session. Messages are exchanged through the XML format.

FIGURES 5A-B illustrate exemplary messages for provisioning data services for a data call in a wireless network. Referring to FIGURE 5A, the DATAORG is sent by the air agent 68 to the ISCP agent 94 to request the data session origination treatment on behalf of a registered mobile device 44. Referring to FIGURE 5B, the dataorg message is the response from the ISCP agent 84.

FIGURES 6A-B illustrate exemplary messages for initiating data transfer for a data call in a wireless network. Referring to FIGURE 6A, the DATABEGIN message is sent by the air agent 68 to the MSG/ISCP agents 84 while originating a data session through the air gateway 62. This trigger is sent when a PPP session is established and data transfer is started. Referring to FIGURE 6B, the databegin message is the response from the ISCP agent 94.

FIGURES 7A-B illustrate exemplary messages for terminating data transfer for a data call in a wireless network. Referring to FIGURE 7A, the DATAEND message is sent by the air agent 68 to the ISCP/MSG agents 84. This trigger is sent after a PPP session is cleared. Referring to FIGURE 7B, the dataend message is the response from the ISCP agent 94.

FIGURES 8A-B illustrate exemplary messages for dataclear services for data call in a wireless network. Referring to FIGURE 8A, the DATACLEAR message occurs in

the middle of a call. The message is sent from the MSG/ISCP agents 84 to the air agent 68. The message is network generated and asynchronous. After receiving the message from the ISCP agent 94, the air agent 68 starts the clearing procedures. These procedures include the clear messages which are sent to the air gateway 62. Referring to FIGURE 8B, the dataclear message is the response from the air agent 68.

FIGURES 9A-B illustrate exemplary messages for forward direction transmission access services for a data call in a wireless network. Referring to FIGURE 9A, the FWDBYTEXD message is sent by the air agent 68 to the MSG/ISCP agents 84 during a data session. The air gateway 62 is set up to count the number of packets received from the mobile device 44. If the total volume of the bytes in the session exceeds the number of bytes present by the ISCP agent 94, then a trigger is sent to the ISCP agent 94. A notification message is sent from the air gateway 62 to the air agent 68 after the detection. The air agent 68 subsequently sends a trigger to the ISCP agent 94 about this event. Also, when the number of bytes exceeds the present value, all of the subsequent packets are discarded, except for packets already queued in the transmit queues. Referring to FIGURE 9B, the fwdbytexd message is the response from the ISCP agent 94.

FIGURES 10A-B illustrate exemplary messages for reverse direction transmission access services for a data call in a wireless network. Referring to FIGURE 10A, the REVBYTEXD message is sent by the air agent 68 to the MSG/ISCP agents 84 during a data session. The air gateway 62 is set up to count the number of packets

transmitted to the mobile device 44. If the total volume of the bytes in the session exceeds the number of bytes preset by the ISCP agent 94, then a trigger is sent to the ISCP agent 94. A notification message is sent from the air gateway 62 to the air agent 68 after the detection. The air agent 68 subsequently sends a trigger to the ISCP agent 94 about the event. Also, when the number of bytes exceeds the preset value, all subsequent packets are discarded. except for packets already queued in the transmit queues. Referring to FIGURE 10B, the revbytexd message is the response from the ISCP agent 94.

FIGURES 11A-B illustrate exemplary messages for time access services for a data call in a wireless network. Referring to FIGURE 11A, the TIMEEXD message is sent by the air agent 68 to the MSG/ISCP agents 84 during a data session. The air gateway 62 is set up to count the duration of the session. If the total duration of the session exceeds the time preset by the ISCP agent 94, then a trigger is sent to the ISCP agent 94. A notification message is sent from the air gateway 62 to the air agent 68 after the detection. The air gateway 64 subsequently sends a trigger to ISCP agent 94 about the event. When the duration exceeds the preset value, all subsequent packets are discarded with packets already queued in the transmit queues being transmitted. Referring to FIGURE 11B, the timeexd message is the response from the ISCP agent 94.

FIGURES 12A-B illustrate exemplary messages for URL matching services for a data call in a wireless network. Referring to FIGURE 12A, the URLmatch message occurs during the middle of the call. This trigger is sent from the air agent 68 to the MSG/ISCP agents 84. The air

gateway 62 detects that a URL from a list provided by the
ISCP/MSG agents 84 is matched. A notification message is
sent from the air gateway 62 to the air agent 68 after
the detection. The air agent 68 subsequently sends a
5 trigger to the ISCP agent 94 about the event. Referring
to FIGURE 12B, the URLmatch is the response from the ISCP
agent 84.

FIGURES 13A-B illustrate exemplary messages for
location change services for a data call in a wireless
10 network. Referring to FIGURE 13A, the LOCCHNG message is
sent from the air agent 68 to the MSG/ISCP agents 84 when
the mobile device 44 has moved from one sector to another
sector or other specified location-based event has
occurred. Referring to FIGURE 13B, the locchng message
15 is the response from the ISCP agent 94.

FIGURES 14A-B illustrate exemplary messages for
multiplematch services for a data call in a wireless
network. Referring to FIGURE 14A, the MULTIMATCH message
is sent when one or more conditions detected by the air
20 gateway 62 and/or air agent 68 are matched. Referring to
FIGURE 14B, the multimatch message is the response from
the ISCP agent 94.

FIGURES 15A-B illustrate exemplary messages for URL
change services for a data call in a wireless network.
25 Referring to FIGURE 15A, the URLCHNG message is sent from
the air agent 68 to the MSG/ISCP agents 84. The air
gateway 62 detects that there is a change in the URL
being accessed by the air gateway 62. A notification
message is sent from the air gateway 62 to the air agent
30 68 after detection. The air agent 68 subsequently sends
a trigger to the ISCP agent 94 about the event.

Referring to FIGURE 15B, the urlchng message is the response from the ISCP agent 94.

FIGURE 16A-B illustrate exemplary messages for data alert services for a data call in a wireless network. Referring to FIGURE 16A, a DATALEERT message is sent from the MSG/ISCP agents 84 to the mobile device 44/air agent 68. The alerts include advertisements, preset notifications and other announcements. In one embodiment, an XML file containing the alert information is sent from the ISCP agent 94. This XML data file is sent to the already running application on the mobile device 44, such as a screen running an HTTP session. Referring to FIGURE 16B, the dataalert message is the response from the mobile device 44.

FIGURE 17A-B illustrate exemplary messages for facility status services for a data call in a wireless network. Referring to FIGURE 17A, the FACLCHNG message is sent from the air agent 68 to the MSG/ISCP agents 84 when a change in air gateway ID/air agent is detected due to handoff, a change in bandwidth in the middle of a session has occurred, such as when the mobile device requests additional channels and/or bandwidth, or resource depletion occurs due to congestion, links down and/or rerouting of data. Referring to FIGURE 17B, the faclchng message is a response from the ISCP agent 94.

FIGURES 18A-U illustrate parameters for the service messages in accordance with a particular embodiment of the present invention. Specifically, FIGURE 18A illustrates message identifiers, 18B illustrates data transaction capabilities, 18C illustrates action responses, 18D illustrates call types, 18E illustrates triggers and 18F illustrates trigger actions. FIGURE 18G

illustrates the IP address of the trigger component, 18H illustrates the URL address of the trigger component, 18I illustrates the trigger component header, 18J illustrates the trigger component type and 18K illustrates the user name. FIGURE 18L illustrates the mobile IP addresses, 18M the data session initiation time stamps, 18N the data session termination time stamps, 18O the URL match time stamps, 18P the last URL accessed by a user, 18Q the current URL accessed by a user, 18R the release reason, 18S the reasons for facility change, 18T change facilities and 18U session records. It will be understood that other or different messages and message parameters may be used for providing services to data calls without departing from the scope of the present invention.

Although the present invention has been described with several embodiments, various changes and modifications may be suggested to one skilled in the art. It is intended that the present invention encompass such changes and modifications as fall within the scope of the appended claims.

WHAT IS CLAIMED IS:

1. A method for providing services for wireless data calls, comprising:

5 monitoring a wireless data call for a predefined event associated with a service for the wireless data call; and

initiating the service for the wireless data call in response to detecting the predefined event for the wireless data call.

10

2. The method of Claim 1, wherein the predefined event comprises a uniform resource locator (URL) match.

15

3. The method of Claim 1, wherein the predefined event comprises a uniform resource locator (URL) change.

20

4. The method of Claim 1, wherein the predefined event comprises use of transmission resources in excess of a predefined amount.

25

5. The method of Claim 1, wherein the predefined event comprises a use of transmission resources in a forward direction from a mobile device to a wireless network in excess of a predefined amount.

30

6. The method of Claim 1, wherein the predefined event comprises a use of transmission resources in a reverse direction from a wireless network to a mobile device in excess of a predefined amount.

7. The method of Claim 1, wherein the predefined event comprises a location-based event.

8. The method of Claim 1, wherein the predefined event comprises a location change of a mobile device for the wireless data call.

5

9. The method of Claim 1, further comprising:

monitoring the wireless data call for a plurality of predefined events together associated with a service for the wireless data call; and

10

initiating the service for the data call in response to detecting a predefined number of the predefined events.

10. The method of Claim 1, further comprising:

15

monitoring a wireless network maintaining the wireless data call for a network-based event associated with a network directed service for the wireless data call; and

20

initiating the network directed service for the wireless data call in response to detecting the network-based event.

11. The method of Claim 10, wherein the network-based event comprises a data alert.

25

12. The method of Claim 10, wherein the network-based event comprises a status of facility change.

13. The method of Claim 1, wherein the service comprises a prepaid calling card service.

30

14. The method of Claim 1, wherein the service comprises a volume-limited network access service.

5 15. The method of Claim 1, wherein the service comprises a time-limited network access service.

16. The method of Claim 1, wherein the service comprises a location-based service.

10 17. The method of Claim 1, wherein the service comprises a web filtering service.

15 18. The method of Claim 17, wherein the predefined event comprises requesting access to a web site and the service comprises granting access to the web site.

20 19. The method of Claim 17, wherein the predefined event comprises requesting access to a web site and the service comprises denying access to the web site.

20. The method of Claim 1, wherein the service comprises a automatic web site redirection.

25 21. The method of Claim 1, wherein the service comprises a quality of service (QoS) based billing service.

30 22. The method of Claim 1, wherein the service comprises a uniform resource locator (URL) based billing service.

23. The method of Claim 10, wherein the network directed service comprises announcements from the wireless network.

5 24. The method of Claim 10, wherein the network directed service comprises advertisements from the wireless network.

10 25. The method of Claim 10, wherein the network directed service comprise delivery of news content.

26. The method of Claim 1, further comprising:
 monitoring the wireless data call for a plurality of predefined events, each associated with a service for the wireless data call; and
15 initiating a service for the wireless data call in response to detecting the associated predefined event for the wireless data call.

20 27. The method of Claim 1, wherein the predefined event comprises a service trigger, further comprising retrieving the service trigger from a service agent at setup of the data call.

25 28. The method of Claim 1, wherein the predefined event comprises a service trigger, further comprising:
 retrieving a plurality of service triggers from a service agent for the data call at call setup;
 monitoring the wireless data call for a service
30 trigger; and

5

10

DAL01:540657.2

31. A system for providing services for wireless data calls, comprising:

a computer processable medium; and

5 logic stored on the computer processable medium, the logic operable to monitor a wireless data call for a predefined event associated with a service for the wireless data call and to initiate the service for the wireless data call in response to detection of the
10 predefined event for the wireless data call.

32. The system of Claim 31, wherein the predefined event comprises a uniform resource locator (URL) match.

15 33. The system of Claim 31, wherein the predefined event comprises a uniform resource locator (URL) change.

34. The system of Claim 31, wherein the predefined event comprises use of transmission resources in excess
20 of a predefined amount.

35. The system of Claim 31, wherein the predefined event comprises a use of transmission resources in a forward direction from a mobile device to a wireless
25 network in excess of a predefined amount.

36. The system of Claim 31, wherein the predefined event comprises a use of transmission resources in a reverse direction from a wireless network to a mobile
30 device in excess of a predefined amount.

37. The system of Claim 31, wherein the predefined event comprises a location-based event.

5 38. The system of Claim 31, wherein the predefined event comprises a location change of a mobile device for the wireless data call.

10 39. The system of Claim 31, to logic further operable to monitor the wireless data call for a plurality of predefined events together associated with a service for the wireless data call and to initiate the service for the data call in response to detecting all of the predefined events.

15 40. The system of Claim 31, the logic further operable to monitor a wireless network maintaining the wireless data call for a network-based event associated with a network directed service for the wireless data call and to initiate the network directed service for the
20 wireless data call in response to detecting the network-based event.

25 41. The system of Claim 40, wherein the network-based event comprises a data alert.

42. The system of Claim 40, wherein the network-based event comprises a status of facility change.

30 43. The system of Claim 31, wherein the service comprises a prepaid calling card service.

44. The system of Claim 31, wherein the service comprises a volume-limited network access service.

5 45. The system of Claim 31, wherein the service comprises a time-limited network access service.

46. The system of Claim 31, wherein the service comprises a location-based service.

10 47. The system of Claim 31, wherein the service comprises a web filtering service.

15 48. The system of Claim 47, wherein the predefined event comprises requesting access to a web site and the service comprises granting access to the web site.

20 49. The system of Claim 47, wherein the predefined event comprises requesting access to a web site and the service comprises denying access to the web site.

50. The system of Claim 31, wherein the service comprises a automatic web site redirection.

25 51. The system of Claim 31, wherein the service comprises a quality of service (QoS) based billing service.

30 52. The system of Claim 31, wherein the service comprises a uniform resource locator (URL) based billing service.

53. The system of Claim 40, wherein the network directed service comprises announcements from the wireless network.

5 54. The system of Claim 40, wherein the network directed service comprises advertisements from the wireless network.

10 55. The system of Claim 40, wherein the network directed service comprise delivery of news content.

15 56. The system of claim 31, the logic further operable to monitor the wireless data call for plurality of predefined events, each associated with a service for the wireless data call, and to initiate a service for the wireless data call in response to detecting the associated predefined event for the wireless data call.

20 57. The system of claim 31, wherein the predefined event comprises a service trigger, the logic further operable to retrieve the service trigger from a service agent at setup of the data call.

25 58. The system of claim 31, wherein the predefined event comprises a service trigger, the logic further operable to retrieve a plurality of service triggers from a service agent for the data call at call setup, monitor the wireless data call for a service trigger, and initiate a service associated with the service trigger
30 for the wireless data call in response to detecting the service trigger.

59. The system of claim 31, the logic further operable to monitor content of the data call for the predefined event.

5 60. The method of claim 31, the logic further
operable to monitor content of the data call in real-time
for the predefined event.

61. A system for providing services for wireless data calls, comprising:

5 means for monitoring a wireless data call for a predefined event associated with the service for the wireless data call; and

means for initiating the service for the wireless data call in response to detection of the predefined event for the wireless data call.

10

62. The system of Claim 61, wherein the predefined event comprises a uniform resource locator (URL) match.

63. The system of Claim 61, wherein the predefined event comprises a uniform resource locator (URL) change.

15

64. The system of Claim 61, wherein the predefined event comprises use of transmission resources in excess of a predefined amount.

20

65. The system of Claim 61, wherein the predefined event comprises a use of transmission resources in a forward direction from a mobile device to a wireless network in excess of a predefined amount.

25

66. The system of Claim 61, wherein the predefined event comprises a use of transmission resources in a reverse direction from a wireless network to a mobile device in excess of a predefined amount.

30

67. The system of Claim 61, wherein the predefined event comprises a location-based event.

68. The system of Claim 61, wherein the predefined event comprises a location change of a mobile device for the wireless data call.

5

69. The system of Claim 61, further comprising:

means for monitoring the wireless data call for a plurality of predefined events together associated with a service for the wireless data call; and

10 means for initiating the service for the data call in response to detecting all of the predefined events.

70. The system of Claim 61, further comprising:

15 means for monitoring a wireless network maintaining the wireless data call for a network-based predefined event associated with a network directed service for the wireless data call; and

20 means for initiating the network directed service for the wireless data call in response to detecting the network-based predefined event.

71. The system of Claim 70, wherein the network-based predefined event comprises a data alert.

25 72. The system of Claim 70, wherein the network-based predefined event comprises a status of facility change.

30 73. The system of Claim 61, wherein the service comprises a prepaid calling card service.

74. The system of Claim 61, wherein the service comprises a volume-limited network access service.

5 75. The system of Claim 61, wherein the service comprises a time-limited network access service.

76. The system of Claim 61, wherein the service comprises a location-based service.

10 77. The system of Claim 61, wherein the service comprises a web filtering service.

15 78. The system of Claim 77, wherein the predefined event comprises requesting access to a web site and the service comprises granting access to the web site.

20 79. The system of Claim 77, wherein the predefined event comprises requesting access to a web site and the service comprises denying access to the web site.

80. The system of Claim 61, wherein the service comprises a automatic web site redirection.

25 81. The system of Claim 61, wherein the service comprises quality of service (QoS) based billing services.

30 82. The system of Claim 61, wherein the service comprises uniform resource locator (URL) based billing services.

83. The system of Claim 70, wherein the network directed service comprises announcements from the wireless network.

5 84. The system of Claim 70, wherein the network directed service comprises advertisements from the wireless network.

10 85. The system of Claim 70, wherein the network directed service comprise delivery of news content.

86. A wireless access system, comprising:

5 wireless signaling management system and a gateway operable to establish and maintain a wireless data call between a mobile device and the Internet;

the wireless signaling management system operable to communicate with a network service layer to provision the gateway with service triggers for the wireless data call; and

10 the gateway operable to monitor content of the wireless data call for the service triggers and to initiate service logic associated with a service trigger upon detection of the service trigger for the wireless data call.

15 87. The wireless access system of Claim 86, the wireless signaling management system further operable to monitor the network service layer for network-directed service triggers for the data call and to initiate service logic associated with a network-directed service trigger upon detection of the network-directed service trigger for the data call.

20 88. The wireless access system of Claim 86, wherein the service logic is operable to perform prepaid calling card services.

25 89. The wireless access system of Claim 86, wherein the service logic is operable to perform location based services.

90. The wireless access system of Claim 86, wherein the service logic is operable to perform web filtering services.

5 91. The wireless access system of Claim 86, wherein the service logic is operable to perform quality of service (QoS) based billing services.

10 92. The wireless access system of Claim 86, wherein the service logic is operable to perform uniform resource locator (URL) based billing services.

15 93. The wireless access system of Claim 86, wherein the wireless signaling management system comprises an air agent.

20 94. The wireless access system of Claim 86, wherein the air gateway is operable to monitor content of the wireless data call for the service triggers in real-time and to initiate service logic associated with a service trigger upon detection of the service trigger for the wireless data call.

95. A system for providing services for wireless data calls, comprising:

means for monitoring a wireless data call for a predefined event associated with a service for the wireless data call; and

means for initiating the service for the wireless data call in response to detecting the predefined event for the wireless data call.

96. The system of Claim 95, further comprising:

means for monitoring the wireless data call for a plurality of predefined events together associated with a service for the wireless data calls; and

means for initiating the service for the data call in response to detecting a predefined number of the predefined events.

97. The system of Claim 95, further comprising:

means for monitoring a wireless network maintaining the wireless data call for a network-based event associated with a network directed service for the wireless data call; and

means for initiating the network directed service for the wireless data call in response to detecting the network-based event.

98. The system of Claim 95, further comprising:

means for monitoring the wireless data call for a plurality of predefined events, each associated with a service for the wireless data call; and

means for initiating a service for the wireless data call in response to detecting the associated predefined event for the wireless data call.

5 99. The system of Claim 95, wherein the predefined event comprises a service trigger, further comprising means for retrieving the service trigger from a service agent at setup of the data call.

10 100. The system of Claim 95, wherein the predefined event comprises a service trigger further comprising:

 means for retrieving a plurality of service triggers from a service agent for the data call at call set up;

15 means for monitoring the wireless data call for a service trigger; and

 means for initiating a service associated with the service trigger for the wireless data call in response to detecting the service trigger.

20 101. The system of Claim 95, further comprising means for monitoring content of the data call for the predefined event.


25 102. The system of Claim 95, further comprising means for monitoring content of the data call in real-time for the predefined event.

METHOD AND SYSTEM FOR PROVIDING
SERVICES FOR WIRELESS DATA CALLS

ABSTRACT OF THE INVENTION

5 A method and system for providing services for
wireless data calls includes monitoring a wireless data
call for a predefined event associated with a service for
the wireless data call. The service is initiated for the
wireless data call in response to detecting the
predefined event for the data call. The predefined event
may comprise a uniform resource locator (URL) match or
10 change, excess use of transmission or time resources, a
location change of a mobile device for the wireless data
call, a network event, or a combination of any or all
suitable events.

FIG. 1







FIG. 3A*FIG. 5A*

XML: DATA ORG		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Call Type	M	Data Call
Calling Party Number	M	
Called Party Number	O	
Transaction Capability	M	List of triggers supported by AA at current time

FIG. 3B





FIG. 4A



TO FIG. 4B

TO FIG. 4C

FROM FIG. 4B




FIG. 5B

XML: data org		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
Call Type	M	
Action Response	M	If denied, reason is included
Triggers	O	

FIG. 6A

XML: DATA BEGIN		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Call Type	M	
Mobile' IP address	O	
Username	O	username@realm.com
Data Session Initiation Time Stamp	M	

FIG. 6B

XML: data begin		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Call Type	M	
Action Response	M	Why data session is rejected

FIG. 7A

XML: DATA END		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Call Type	M	
Session ID	M	
Session Termination Time Stamp	M	
Release Reason	O	
Session Records		Number of packets received, number of packets discarded, number of errors, number of voice call attempts

FIG. 7B

XML: data end		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 Byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	

FIG. 8A

XML: DATA CLEAR		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Call Type	M	
Session ID	M	
Release Reason	O	

FIG. 8B

XML: data clear		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	

FIG. 9A

XML: FWD BY TEXT		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Call Type	M	
Byte Count	M	Number of bytes that can be transmitted

FIG. 9B

XML: fwd by text		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	
Triggers	O	

FIG. 10A

XML: REV BY TEXT		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Call Type	M	
Byte Count	M	Number of bytes that can be transmitted

FIG. 10B

XML: rev by texd		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	
Triggers	O	

FIG. 11A

XML: TIMEEXD		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Call Type	M	
Duration	M	Duration represented by "YearsMonthsDaysHoursMinutesSeconds"

FIG. 11B

XML: timeexd		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	
Triggers	O	

FIG. 12A

XML: URLMATCH		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
Call Type	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
URL Match Time Stamp	O	
Current URL Detected	M	

FIG. 12B

XML: urlmatch		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	
Triggers	O	

FIG. 13A

XML: LOCCHNG		
FIELD	TYPE	COMMENTS
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc. This is the current location.
Type of Change	O	Handoff/sector/administrative boundary
Session ID	M	
Location Change Time Stamp	O	
Previous Location Information	O	

FIG. 13B

XML: locchng		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Session ID	M	
Trigger Action	O	

FIG. 14A

XML: MULTIMATCH		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Time Stamp	O	Year, month, day, hours, minutes and seconds
Triggers	O	
Trigger Information	O	Trigger information is collected for each trigger and concatenated. Eg., matched URL, matched IP and others. Each trigger component will have trigger information.

FIG. 14B

XML: multimatch		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Action Response	O	

FIG. 15A

XML: URLCHNG		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
URL-Change Time Stamp	O	
Last URL Accessed by User	M	
Current URL	M	

FIG. 15B

XML: urlchng		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Triggers	O	

FIG. 16A

XML: DATALERT		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Alert Information	M	An XML file sent from ISCP to Air Agent

FIG. 16B

XML: dataalert		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Action	O	Successfully delivered or an error code denoting that mobile is not accessible.

FIG. 17A

XML: FACLCHNG		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air Agent ID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Reason for Change	O	Handoff/failure/congestion/change in bandwidth
Details of Changed Facilities	O	Link bandwidth, change of QoS, degree of congestion

FIG. 17B

XML: faclchng		
FIELD	TYPE	COMMENTS
Message Identifier	M	
Transaction Identifier	M	Associates a given request and reply
Length	M	2 byte length field
Air AgentID	M	
MIN/IMSI	M	
Location Information	M	This is combination of switch number, Cell ID, Marketing ID, etc.
Session ID	M	
Data Session ID	M	
Trigger Action	O	

FIG. 18A

MESSAGE IDENTIFIER			
MESSAGE	IDENTIFIER	MANDATORY RESPONSE	COMMENTS
DATAORG	1	M	
DATABEGIN	2	0	
DATAEND	3	0	
DATACLEAR	4	0	
URLMATCH	5	0	
URLCHNG	6	0	
FACLCHNG	7	0	
FWDBYTEXD	8	0	
REVBYTEXD	9	0	
TIMEEXD	10	0	
MULTIMATCH	11	0	
LOCCHNG	12	0	
DATALERT	13	0	

FIG. 18B

DATA TRANSACTION CAPABILITY							
Identifier							
Length							
LOCCHNG	DATACLEAR	FACLCHNG	URLCHNG	URLMATCH	DATAEND	DATABEGIN	DATAORG
FWDBYTEXD	REVBYTEXD	TIMEEXD	MULTIMATCH	DATALERT			

FIG. 18C

ACTION RESPONSE	
Identifier	
Length	
Additional reasons for data triggers	
01 Success	
02 Access Denied Reason	

FIG. 18D

CALL TYPE
Identifier
Length
Type of Call 00 Data

FIG. 18E

TRIGGERS		
FIELD	TYPE	COMMENTS
Trigger Identifier	M	See the identifier table
Update	M	1: Update Previous Triggers, 2: Overwrite Existing Triggers
FireType	M	1: One Time 2: Always (when the conditions match)
Form	M	1: DNF 2: CNF
TRIGGER COMPONENTS1	M	
TRIGGER COMPONENTS2	M	
TRIGGER COMPONENTS'N	M	

FIG. 18F

TRIGGER ACTION
Identifier
Length
1) Allow access 2) Deny access 3) Allow access and inform 4) Deny access and inform 5) Service logic IP address 6) Service logic port type 7) Service logic port number 8) Service logic application protocol number

2025-03-26 14:23:43

FIG. 18G

TRIGGER COMPONENT: IP ADDRESS		
FIELD	TYPE	COMMENTS
Trigger Component Header	M	
Type	M	0: Source 1: Destination
Value Type	M	1: Single Value, 2: Range, 3: Multi Value, 4: Not Applicable If it is a range then Value1 is min and Value2 is max
Value1	M	Value of IP Address
Value2	M	Value of IP Address
Value3	M	Value of IP Address
Value'N	M	Value of IP Address

FIG. 18H

TRIGGER COMPONENT: URL		
FIELD	TYPE	COMMENTS
Trigger Component Header	M	
Value1	M	http://www.yahoo.com
Value2	M	http://www-nrc.nokia.com/mail-archive/ext-ip-location/threads.html
Value3	M	http://search.ietf.org/internet-drafts/draft-kankkunen-vompls-fw-00.txt
Value'N	M	http://dailynews.yahoo.com/headlines/business/

FIG. 18I

TRIGGER COMPONENT: HEADER		
FIELD	TYPE	COMMENTS
Type	M	Component type
Negate	M	1: Negate this condition 0: Don't negate
GroupNo	M	Group Number of the Condition (group the trigger component types)

FIG. 18J

TRIGGER COMPONENT: TYPE
1) Origination Request 2) Start of a Session 3) End of a Session 4) IPv4Condition 5) Port Condition 6) URL Match Condition 7) URL Change Condition 8) Forward Byte Count Condition 9) Reverse Byte Count Condition 10) Location Condition 11) Session Time Condition 12) Application Condition 13) Trigger Action

FIG. 18K

USERNAME
Identifier
Length
"username@realm.com (represented as ASCII string)"
username@realm.com (represented as ASCII string)
username@realm.com (represented as ASCII string)
username@realm.com (represented as ASCII string)
"n characters"
username@realm.com (represented as ASCII string)"

FIG. 18L

MOBILE'S IP ADDRESS
Identifier
Length
IP Version 4 or 6 (4 bytes or 12 bytes)
IP Address

00520 2836360

FIG. 18M

DATA SESSION INITIATION TIME STAMP
Identifier
Length
"YearMonthDayHoursMinutesSeconds"

FIG. 18N

DATA SESSION TERMINATION TIME STAMP
Identifier
Length
"YearMonthDayHoursMinutesSeconds"

FIG. 18O

URL MATCH TIME STAMP
Identifier
Length
"YearMonthDayHoursMinutesSeconds"

FIG. 18P

LAST URL ACCESSED BY USER
Identifier
Length
"http://www.ipmobile.com"

FIG. 18Q

CURRENT URL ACCESSED BY USER
Identifier
Length
"http://www.ipmobile.com"

FIG. 18R

RELEASE REASON
Identifier
Length
Reason 00 Facilities not Available at the Terminating End 01 Network Resources not Available 02 Network Resources Congestion 03 Route not Available 04 Incoming Voice Call

FIG. 18S

REASON FOR FACILITIES CHANGE
Identifier
Length
Reason 00 Handoff 01 Failure of Link 02 Buffer Congestion in AirGateway 03 Change in Bandwidth 04 Change in QoS

FIG. 18T

CHANGED FACILITIES
Identifier
Length
Reason <ol style="list-style-type: none">1. Target AirGateway2. Target AirAgent3. Failed Link ID4. New QoS5. New Bandwidth6. Degree of Congestion

FIG. 18U

SESSION RECORDS
Identifier
Length
Records for Session <ol style="list-style-type: none">1. Number of FWD Packets/Bytes Received2. Number of FWD Packets/Bytes Received3. Number of FWD Packets/Bytes Discarded4. Number of REV Packets/Bytes Received5. Number of REV Packets/Bytes Received6. Number of REV Packets/Bytes Discarded7. Time Duration of the Session8. Number of CRC Errors

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; that I believe I am the original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention or design entitled METHOD AND SYSTEM FOR PROVIDING SERVICES FOR WIRELESS DATA CALLS, the specification of which (check one):

 X is attached hereto; or
 was filed on as Application Serial No. and was
amended on (if applicable);

that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above; and that I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Number</u>	<u>Country</u>	<u>Date Filed</u>	<u>Priority Claimed (Yes) (No)</u>
-----NONE-----			

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

<u>Application</u> <u>Serial Number</u>	<u>Date Filed</u>	<u>Status</u>
--	-------------------	---------------

-----NONE-----

I hereby appoint:

Jerry W. Mills	Reg. No. 23,005
Robert M. Chiaviello, Jr.	Reg. No. 32,461
Ann C. Livingston	Reg. No. 32,479
Thomas R. Felger	Reg. No. 28,842
Charles S. Fish	Reg. No. 35,870
Kevin J. Meek	Reg. No. 33,738
T. Murray Smith	Reg. No. 30,222
Barton E. Showalter	Reg. No. 38,302
David G. Wille	Reg. No. 38,363
Bradley P. Williams	Reg. No. 40,227
Terry J. Stalford	Reg. No. 39,522
Christopher W. Kennerly	Reg. No. 40,675
Harold E. Meier	Reg. No. 22,428
Douglas M. Kubehl	Reg. No. 41,915
Samir A. Bhavsar	Reg. No. 41,617
Thomas R. Nesbitt, Jr.	Reg. No. 22,075
James J. Maune	Reg. No. 26,946
Roger J. Fulghum	Reg. No. 39,678
Scott F. Partridge	Reg. No. 28,142
James B. Arpin	Reg. No. 33,470
Jay B. Johnson	Reg. No. 38,193
Robert W. Holland	Reg. No. 40,020
James L. Baudino	Reg. No. 43,486
Tara D. Knapp	Reg. No. 43,723
William R. Borchers	Reg. No. 44,549
Brian W. Oaks	Reg. No. 44,981
Luke K. Pedersen	Reg. No. 45,003
Matthew B. Talpis	Reg. No. 45,152
David M. Doyle	Reg. No. 43,596
Keiko Ichiye	Reg. No. 45,460
Jeffery D. Baxter	Reg. No. 45,560
Thomas A. Beaton	Reg. No. 46,543
Kurt M. Pankratz	Reg. No. 46,977
Brian E. Szymczak	Reg. No. 47,120
Thomas J. Frame	Reg. No. 47,232

Patent Agents:

Brian A. Dietzel	Reg. No. 44,656
Kevin R. Imes	Reg. No. 44,795

all of the firm of Baker Botts L.L.P., my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith and to file and prosecute any international patent applications filed thereon before any international authorities under the Patent Cooperation Treaty.

Send Correspondence To:

Baker Botts L.L.P.
2001 Ross Avenue
Dallas, Texas 75201-2980

Direct Telephone Calls To:

Terry J. Stalford
at 214.953.6477
Attorney Docket No. 062891.0482 (IPM 3422)

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of the first inventor

Ramanamurthy (nmi) Dantu

Inventor's signature

D. Ramanamurthy

Date

10/20/00

Residence (City, County, State)

Richardson, Collin County, Texas

Citizenship

Canada

Post Office Address

3103 Kingsbury Drive
Richardson, Texas 75082

Full name of additional joint inventor, if any

Pulin R. Patel

Inventor's signature

PR Patel

Date

10/18/2000

Residence (City, County, State)

McKinney, Collin County, Texas

Citizenship

Great Britain

Post Office Address

2213 Whitney Lane
McKinney, Texas 75070

Full name of additional joint inventor, if any

Pravir A. Patel

Inventor's signature

Pravir A. Patel

Date

10/18/2000

Residence (City, County, State)

Plano, Collin County, Texas

Citizenship

India

Post Office Address

7101 Chase Oaks Boulevard, Apt. #112
Plano, Texas 75025

Full name of additional joint inventor, if any

Alexander G. Garbuz

Inventor's signature

AG Garbuz

Date

10/19/2000

Residence (City, County, State)

Plano, Collin County, Texas

Citizenship

United States of America

Post Office Address

3700 Penland Street
Plano, Texas 75023

5

Full name of additional joint inventor, if any

Jerzy (nmi) Miernik

Inventor's signature

Jerzy Miernik
10/18/2000

Date

Residence (City, County, State)

Allen, Collin County, Texas

Citizenship

Canada

Post Office Address

402 Watters Crossing Court
~~McKinney~~, Texas 75013
Allen

Full name of additional joint inventor, if any

Achal R. Patel

Inventor's signature

Achal Patel
10/18/2000

Date

Residence (City, County, State)

McKinney, Collin County, Texas

Citizenship

United States of America

Post Office Address

2302 Sherbrooke Lane
McKinney, Texas 75070

Full name of additional joint inventor, if any

BALAJI. S. HOLUR
~~Balaji~~ S. Holur Shalaji

Inventor's signature

Shalaji
10/18/2000

Date

Residence (City, County, State)

Plano, Collin County, Texas

Citizenship

India

Post Office Address

7305 Randall Way
Plano, Texas 75025